

F156PET-T42

(10-points)(Air Bonding)



Features

- 15.6" PCAP Multi-Touch Display
- 1920 x 1080, 450 cd/m², LVDS Interface
- Supports 10-points touch
- High transparency and excellent display clarity
- Fast response and high sensitivity




Image above for reference only

MADE IN TAIWAN

Specification

Model	F156PET-T42	
TFT LCD	Inch	15.6"
	Resolution	1920X 1080 (FHD)
	Signal Interface	eDP
	Brightness	450 cd/m ² (Typ.)
	Viewing Angle	89/89/89/89
	Contrast	1000 : 1 (Typ.)
	B/L Life Time (Hr)	50K (Min.)
	Backlight Driver	Built-in
PCAP Touch	Structure (Glass Thickness)	G/G (2.00 mm)
	Touch Control IC	EETI, EXC81W60
	FPC Type	COF
	Interface	USB / I2C
	Surface Treatment	Clear
	Transparency	≥85%
	Surface Hardness	≥7H
	Allow Touch Points	≤10 Points
Touch Display	Input Method	Finger, Gloved, Stylus
	Bonding Type	Air Bonding
	View Area (mm)	345.24 x 194.68
	Outline Dimension (mm)	375.24 x 240.68 x 9.60
	Weight	0.97 Kg (Typ.)
	Operating Temperature	0 ~ 60 °C
	Storage Temperature	-20 ~ 70 °C
	OS	Android, Linux, MacOS, Windows

Dimension



Packing Volume Reference

Packaging	Sample			Full Box	1 Pallet
QTY	1 pc	2 pcs	3 pcs	10 pcs	-
N.W. (Kg)	0.97	1.94	2.91	9.70	-
G.W. (Kg)	1.93	2.90	3.87	11.20	-
Dimension (mm)	470 x 320 x 155	470 x 320 x 155	470 x 320 x 155	470 x 370 x 354	-