

F156PET-T43

(10-points)(Air Bonding)



Features

- 15.6" PCAP Multi-Touch Display
- 1920 x 1080, 450 cd/m², LVDS Interface
- Supports 10-points touch
- High transparency and excellent display clarity
- Fast response and high sensitivity




Image above for reference only

MADE IN TAIWAN

Specification

Model	F156PET-T43	
TFT LCD	Inch	15.6"
	Resolution	1920X 1080 (FHD)
	Signal Interface	LVDS
	Brightness	450 cd/m ² (Typ.)
	Viewing Angle	89/89/89/89
	Contrast	800 : 1 (Typ.)
	B/L Life Time (Hr)	50K (Min.)
	Backlight Driver	Built-in
PCAP Touch	Structure (Glass Thickness)	G/G (2.70 mm)
	Touch Control IC	EETI, EXC81W60
	FPC Type	COF
	Interface	USB / I2C
	Surface Treatment	Clear
	Transparency	≥ 85 %
	Surface Hardness	≥ 7H
	Allow Touch Points	≤ 10 Points
Touch Display	Input Method	Finger, Gloved, Stylus
	Bonding Type	Air Bonding
	View Area (mm)	345.24 x 194.60
	Outline Dimension (mm)	375.24 x 240.68 x 12.40
	Weight	1.47 Kg (Typ.)
	Operating Temperature	-20 ~ 70 °C
	Storage Temperature	-30 ~ 80 °C
	OS	Android, Linux, MacOS, Windows

Dimension



Packing Volume Reference

Packaging	Sample				Full Box	1 Pallet
QTY	1 pc	2 pcs	3 pcs		10 pcs	-
N.W. (Kg)	1.47	2.94	3.87		14.70	-
G.W. (Kg)	2.43	3.90	4.83		16.20	-
Dimension (mm)	470 x 320 x 155	470 x 320 x 155	470 x 320 x 155		470 x 370 x 354	-