

F156PET-TA2

Title	15.6-inches Touch Display Product Specifications
Model Name	F156PET-TA2
Version	0

Customer	
Approved by	Date
Notice: This Specification is subject to change without notice.	

Approved By	Prepared By
ZOE NIEN 2026-05-22	ALLEN FANG 2026-05-22



REVISION HISTORY

Version	ECN No.	Description of Changes	Date	Prepared
0		Draft specification first edition	2026-05-22	Allen Fang

CONTENTS

1. GENERAL DESCRIPTION.....	4
1.1. INTRODUCTION	4
1.2. FEATURES	4
1.3. APPLICATION.....	4
2. GENERAL SPECIFICATIONS	5
3. ABSOLUTE MAXIMUM RATINGS	6
4. ELECTRICAL CHARACTERISTICS.....	6
4.1. LCD MODULE	6
4.1.1. LCD BLOCK DIAGRAM.....	6
4.1.2. POWER SPECIFICATION.....	7
4.1.3. LVDS DC ELECTRICAL CHARACTERISTICS.....	8
4.1.4. LCD BACKLIGHT UNIT	9
4.1.5. LCD INPUT TERMINAL PIN ASSIGNMENT (CN1)	9
4.1.6. LED BACKLIGHT UNIT (CN2)	11
4.1.7. PIXEL FORMAT IMAGE.....	12
4.1.8. THE LCD INPUT DATA FORMAT	13
4.1.9. LCD TIMING CHARACTERISTICS	14
4.1.10. LCD INPUT TIMING DIAGRAM	14
4.1.11. POWER SEQUENCE FOR LCD	15
4.2. TOUCH PANEL.....	16
4.2.1. TOUCH DRIVER PIN ASSIGNMENT	16
5. OPTICAL CHARACTERISTICS	17
6. RELIABILITY TEST ITEMS	20
7. LABEL.....	20
8. MECHANICAL CHARACTERISTICS	21
9. ENGINEERING DRAWING.....	23



1. GENERAL DESCRIPTION

1.1.INTRODUCTION

F156PET-TA2 is a 15.6" color active matrix TFT LCD module G156HAN04.0 with projected capacitive multi-touch B156PFU-E15 air bonding.

The display format is intended to support the 16:9 FHD mode (1920(H) x 1080(V)) screen and 16.7M colors (LVDS RGB 8-bits) with LED backlight driving circuit.

1.2.FEATURES

- 16:9 FHD (1920x1080) resolution
- Long life LED backlight (50k hrs)
- Industrial application
- RoHS product

1.3.APPLICATION

- TFT LCD monitor
- Industrial application



2. GENERAL SPECIFICATIONS

Parameter	Specification	Unit	Remarks
Active Area Size	15.6	inch	
Display Area	344.16(H) x 193.59 (V)	mm	
Outline Dimension	375.24 (H) x 240.68 (V) x 13.62 (D)	mm	D:PCAP+LCM
Weight	1270	g	Typ.
Driver Element	a-Si TFT active matrix	-	
Display Colors	16.7M (RGB 8-bits)	Colors	
Electrical Interface	2-ch LVDS	-	
Number of Pixels	1920 (H) x 1080 (V)	pixels	
Pixel Pitch	0.17925 (H) x 0.17925(W)	mm	
Pixel Arrangement	RGB vertical stripe	-	
Display Mode	AHVA / Normal Black	-	
Color Gamut	72	%	
Touch Technology	Projected Capacitive Multi-Touch Panel	-	
Touch Method	Finger or exclusive pen	-	
Numbers of Touch	10	Points	
Touch FPC Type	COF	-	
Touch Sensor Glass Type	Strengthening Glass	-	
Touch Controller IC	EETI, EXC81W60	-	
Touch Driver Interface	USB & I ² C	-	
Support OS	Android, Linux, Win7, Win8, Win10, XP	-	

3. ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit.

Parameter	Symbol	Min.	Max.	Unit
Logic/LCD Drive Voltage	V_{DD}	-0.3	+4.0	V
LCD Input Signal Voltage	V_{signal}	-0.3	+4.0	V
LED Input Voltage	LED_V_{DD}	-0.3	+13.2	V
LED Control Signal Voltage	LED_EN, PWM	-0.3	+6.0	V
Operating Temperature	T_{op}	-20	+70	°C
Operating Humidity	H_{op}	10	90	%RH
Storage Temperature	T_{st}	-20	+70	°C
Storage Humidity	H_{st}	10	90	%RH
Touch DC Supply Voltage	I ² C	-0.3	3.6	V
Touch DC Supply Voltage	USB	-0.3	6.0	V


Note: Maximum Wet-Bulb temperature should be 39°C and no condensation.

4. ELECTRICAL CHARACTERISTICS

4.1. LCD MODULE

4.1.1. LCD BLOCK DIAGRAM

The following diagram shows the function block of the 15.6 inches wide Color TFT/LCD module.



4.1.2. POWER SPECIFICATION

LCD Input power specifications are as below;

The power specifications are measured under 25°C and frame frequency under 60Hz.


Symbol	Parameter	Min.	Typ.	Max.	Units	Remark
VDD	Logic/LCD Drive Voltage	3.0	3.3	3.6	V	
PDD	VDD Power	-	1.75	2.11	W	All White pattern (VDD=3.3V, at 60Hz), Note 1
IDD	IDD Current	-	0.53	0.64	A	All White pattern (VDD=3.3V, at 60Hz), Note 2
IRush	Inrush Current	-	-	2000	mA	Note 1
VDDrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	100	mV p-p	All White pattern (VDD=3.3V, at 60Hz)

Note 1: Maximum Measurement Condition: White pattern at 3.3V driving voltage. ($P_{max} = V_{3.3} \times I_{white}$)

Note 2: Typical Measurement Condition: Mosaic Pattern

Current fuse is built in a module. Current capacity of power supply for VDD should be larger than 1.5A, so that the fuse can be opened at the trouble of electrical circuit of module.

Note 3: Measure Condition



4.1.3. LVDS DC ELECTRICAL CHARACTERISTICS


Input signals shall be low or High-impedance state when VDD is off.

Symbol	Item	Min.	Typ.	Max.	Unit	Remark
V _{TH}	Differential Input High Threshold			+100	mV	V _{CM} =1.2V
V _{TL}	Differential Input Low Threshold	-100			mV	V _{CM} =1.2V
V _{ID}	Input Differential Voltage	100		600	mV	
V _{ICM}	Differential Input Common Mode Voltage	1.0	1.2	1.5	V	V _{TH} /V _{TL} =+-100mV


Note: LVDS Signal Waveform

$V_P - V_N = |V_{ID}| > V_{TH} = \text{"High"}$
 $V_P - V_N = -|V_{ID}| < V_{TL} = \text{"Low"}$

Single-end Signal



Differential Signal



4.1.4. LCD BACKLIGHT UNIT

Parameter	Symbol	Min.	Typ.	Max.	Units	Remark
LED Power Supply	VLED	10.8	12	13.2	V	Define as Connector Interface (Ta=25°C)
LED Input Current	ILED		2.52		A	
Swing Voltage	F _{PWM}	3	3.3	5	V	
High Voltage		3	3.3	5	V	
Low Voltage				0.8	V	
Dimming Frequency		200		20K	Hz	
Dimming Duty	200Hz~5KHz	5	-	100	%	
	5KHz~20KHz	15		100	%	
Backlight Power Consumption	PLED	-	25.14	30.17	W	(Ta=25°C), Vin=12V, Note 2
LED Life-Time	N/A	50,000	-	-	Hour	(Ta=25°C), Note 3, 4

Note 1: Re-commanded system pull up/down resistor no bigger than 10k ohm.

Note 2: Ta means ambient temperature of TFT-LCD module.

Note 3: If G156HAN04.0 module is driven at high ambient temperature & humidity condition. The operating life will be reduced.

Note 4: Operating life means brightness goes down to 50% initial brightness. Min. operating life time is estimated data.

4.1.5. LCD INPUT TERMINAL PIN ASSIGNMENT (CN1)

LVDS Connector

TFT-LCD Connector	Manufacturer	P-TWO	STM
	Part Number	187034-3009	MSBKT2407P30HB
Mating Connector	Manufacturer	JAE or Equivalent	
	Part Number	FI-X30HL (Locked Type)	



Pin	Symbol	Description	Note
1	RXO0-	Negative LVDS differential data input (Odd data)	
2	RXO0+	Positive LVDS differential data input (Odd data)	
3	RXO1-	Negative LVDS differential data input (Odd data)	
4	RXO1+	Positive LVDS differential data input (Odd data)	
5	RXO2-	Negative LVDS differential data input (Odd data)	
6	RXO2+	Positive LVDS differential data input (Odd data)	
7	GND	Ground	
8	RXOCLK-	Negative LVDS differential clock input (Odd data)	
9	RXOCLK+	Positive LVDS differential clock input (Odd data)	
10	RXO3-	Negative LVDS differential data input (Odd data)	
11	RXO3+	Positive LVDS differential data input (Odd data)	
12	RXE0-	Negative LVDS differential data input (Even data)	
13	RXE0+	Positive LVDS differential data input (Even data)	
14	GND	Ground	
15	RXE1-	Negative LVDS differential data input (Even data)	
16	RXE1+	Positive LVDS differential data input (Even data)	
17	GND	Ground	
18	RXE2-	Negative LVDS differential data input (Even data)	
19	RXE2+	Positive LVDS differential data input (Even data)	
20	RXECLK-	Negative LVDS differential clock input (Even data)	
21	RXECLK+	Positive LVDS differential clock input (Even data)	
22	RXE3-	Negative LVDS differential data input (Even data)	
23	RXE3+	Positive LVDS differential data input (Even data)	
24	GND	Must connect to ground	
25	NC	No connection (for AUO test only, Do not connect)	
26	NC	No connection (for AUO test only, Do not connect)	
27	NC	No connection (for AUO test only, Do not connect)	
28	VDD	Power Supply Input Voltage	
29	VDD	Power Supply Input Voltage	
30	VDD	Power Supply Input Voltage	


Note 1: Input signals shall be low or High-impedance state when VDD is off.

4.1.6. LED BACKLIGHT UNIT (CN2)


BLU Connector

Connector Name / Description	Lamp Connector
Manufacturer	STM or compatible
Connector Model Number	MSB24038P8D or compatible
Mating Model Number	P24038P8 or compatible


Pin No.	Symbol	Description
Pin1	VLED	12V Input
Pin2	VLED	12V Input
Pin3	VLED	12V Input
Pin4	GND	GND
Pin5	GND	GND
Pin6	GND	GND
Pin7	VLED_EN	5V-ON, 0V-OFF
Pin8	VPWM_EN	PWM



LVDS (CN1):




BLU Power in (CN2):




4.1.7. PIXEL FORMAT IMAGE

Following figure shows the relationship of the input signals and LCD pixel format.



4.1.8. THE LCD INPUT DATA FORMAT



Note 1: Please follow PSWG.

Note 2: R/G/B data 7: MSB, R/G/B data 0: LSB

Signal Name	Description	Remark
R7 R6 R5 R4 R3 R2 R1 R0	Red Data 7 Red Data 6 Red Data 5 Red Data 4 Red Data 3 Red Data 2 Red Data 1 Red Data 0	Red-pixel Data 8Bits LVDS input MSB: R7 ; LSB: R0
G7 G6 G5 G4 G3 G2 G1 G0	Green Data 7 Green Data 6 Green Data 5 Green Data 4 Green Data 3 Green Data 2 Green Data 1 Green Data 0	Green-pixel Data 8Bits LVDS input MSB: G7 ; LSB: G0
B7 B6 B5 B4 B3 B2 B1 B0	Blue Data 7 Blue Data 6 Blue Data 5 Blue Data 4 Blue Data 3 Blue Data 2 Blue Data 1 Blue Data 0	Blue-pixel Data 8Bits LVDS input MSB: B7 ; LSB: B0
RxCLKIN	LVDS Data Clock	
DE	Data Enable Signal	When the signal is high, the pixel data shall be valid to be displayed.

Note: Output signals from any system shall be low state or High-impedance state when VDD is off.

4.1.9. LCD TIMING CHARACTERISTICS

Basically, interface timing should match the 1920x1080 / 60 Hz manufacturing guide line timing.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Frame Rate		-	-	60	-	Hz
Clock frequency		1/T _{CLOCK}	68.5	70.5	73	MHz
Vertical Section	Period	T _V	1104	1116	1080+A	T _{LINE}
	Active	T _{VD}	1080			
	Blanking	T _{VB}	24	36	A	
Horizontal Section	Period	T _H	1050	1052	960+B	T _{CLOCK}
	Active	T _{HD}	960			
	Blanking	T _{HB}	90	92	B	

Note 1: The above is as optimized setting

Note 2: The maximum clock frequency = $[(960+B) \cdot (1080+A) \cdot 60] < 74.5$ MHz


Note 3: Horizontal related parameters must be constant without variation (H_Sync_Width (T_{HW}), H_Front_Porch (T_{HF}) and H_Back_Porch (T_{HP}) must be constant on each scan line).

Note 4: On vertical blank area, H_Sync_Width (T_{HW}) and H_Total (T_H) must be same as on the V_Active area.

Note 5: Vertical related parameters must be constant without variation. (V_Sync_Width (T_{VW}), V_Front_Porch (T_{VF}) and V_Back_Porch (T_{VP}) must be constant on each video field).


Note 6: The DE timings also must be constant without variation (H/V timing requirements are as same as previous. Blank timing must also be constant).

4.1.10. LCD INPUT TIMING DIAGRAM



4.1.11. POWER SEQUENCE FOR LCD

VDD power and lamp on/off sequence is as below. Interface signals are also shown in the chart. Signals from any system shall be High-impedance state or low level when VDD is off.



Power ON/OFF sequence timing

Parameter	Value			Unit
	Min.	Typ.	Max.	
T1	0.5	-	10	ms
T2	30	40	50	ms
T3	200	-	-	ms
T4	0.5	-	10	ms
T5	10	-	-	ms
T6	10	-	-	ms
T7	0	-	-	ms
T8	10	-	-	ms
T9	-	-	10	ms
T10	110	-	-	ms
T11	0	16	50	ms
T12	-	-	10	ms
T13	1000	-	-	ms

The above on/off sequence should be applied to avoid abnormal function in the display. Please make sure to turn off the power when you plug the cable into the input connector or pull the cable out of the connector.


4.2.TOUCH PANEL

No.	Item	Specification
1	Touch Controller IC	EXC81W60
2	Number of Channel	RX 49 x TX 28
3	Number of Support	10 points Finger Touch
4	FPC Type / Interface	COF / USB & I ² C
5	OS	Android, Linux, Win7, Win8, Win10, XP

Interface	Symbol	Condition	Min.	Typ.	Max.	Unit
I2C	V _{DD}	-	-	3.3	-	V
USB				5		

4.2.1. TOUCH DRIVER PIN ASSIGNMENT

J1 I2C	Pin Definition	J2 USB	Pin Definition
1	RST	1	GND
2	V _{DD} (3.3V)	2	V _{DD} (5V)
3	GND	3	GND
4	INT	4	D+
5	SDA	5	D-
6	SCL		



5. OPTICAL CHARACTERISTICS

The optical characteristics are measured under stable conditions of 25°C (Room Temperature)

Item		Unit	Conditions		Min.	Typ.	Max.	Note
White Luminance		cd/m²	I _{LED} =70mA Center average		800	1000	-	1, 2
Luminance Uniformity		%	9 points		75	80	-	1, 2, 3
Contrast Ratio		-			700	1000	-	1, 4
Response Time		ms	Rising + Falling		-	25	35	1, 5
View Angle		degree	Horizontal CR=10	Right	80	89	-	1, 6
				Left	80	89	-	
			Vertical CR=10	Upper	80	89	-	
				Lower	80	89	-	
Color / Chromaticity Coordinates (CIE 1931)	Red	Rx	CIE 1931		0.605	0.655	0.705	4
		Ry			0.282	0.332	0.382	
	Green	Gx			0.248	0.298	0.348	
		Gy			0.567	0.617	0.667	
	Blue	Bx			0.097	0.147	0.197	
		By			0.012	0.062	0.112	
	White	Wx			0.263	0.313	0.363	
		Wy			0.279	0.329	0.379	
Color Gamut		%			-	72	-	


Note 1: Measurement method

Equipment Pattern Generator, Power Supply, Digital Voltmeter, Luminance meter (SR_3 or equivalent)


Aperture 1° with 50cm viewing distance

Test Point Center

Environment <1 lux



Note 2: The 9 points position



Note 3: The luminance uniformity of 9 points is defined by dividing the maximum luminance values by the minimum test point luminance. And measured by TOPCON SR-3

$$\delta_{w9} = \frac{\text{Minimum Luminance of 9 points}}{\text{Maximum Luminance of 9 points}}$$


Note 4: Definition of contrast ratio:

Contrast ratio is calculated with the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "White" state}}{\text{Brightness on the "Black" state}}$$


Note 5: Definition of response time:

The output signals of BM-7 or equivalent are measured when the input signals are change from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval is between 10% and 90% of amplitudes. Refer to figure as below.



Note 6: Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (ϕ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotate about its center to develop the desired measurement viewing angle.



6. RELIABILITY TEST ITEMS

Test Item		Condition
1	High temperature/Humidity Bias	40°C, 90% 240hrs
2	High temperature storage test	70°C, 240hrs
3	Low temperature storage test	-20°C, 240hrs
4	High temperature operation test	70°C, 240hrs
5	Low temperature operation test	-20°C, 240hrs
6	Thermal Cycle storage test	-20°C(30min)~60°C(30min), 10cycles

7. LABEL

Model No. F156PET-TA2

條碼

SN 3A Z 20 2 21 0 XXX1

W=14mm



L=32mm

字型:Arial (6)

Code: 128

字型 : Arial(8)

Code1, 2 Production location

Code 3 Production version

Code 4, 5 Production year

Code 6 Production month

Code 7, 8 Production day

Code 9 Production code

Colde 10, 11, 12, 13 Serial number

8. MECHANICAL CHARACTERISTICS

Item		Dimension	Unit	Note
Outline Dimension	Horizontal	375.24	mm	PCAP : B156PFU-E15
	Vertical	240.68	mm	
	Depth	2.00	mm	
	Horizontal	363.80	mm	LCD : G156HAN04.0
	Vertical	215.90	mm	
	Depth	10.51(PCB)	mm	
Weight		1270	g	F156PET-TA2
Item		Specification		Remarks
PCAP Viewing Area		345.24 mm x 194.68 mm		
PCAP Sensor Area		358.24 mm x 211.94 mm		
PCAP FPC Length		55.31 mm		
PCAP Input method		Finger or exclusive pen		
PCAP Light Transmission		≥85%		
PCAP Operation force		≤10g		Finger Input
PCAP Hardness of surface		≥7H		Pressure 500gf test
PCAP Surface Treatment		Clear Type		



Front View

(TBD)

Product Specification

F156PET-TA2

Back View

(TBD)

9. ENGINEERING DRAWING

