



- ☐ Draft Specifications
☒ Preliminary Specifications
☐ Final Specifications

Title	17.0-inches Touch Display Product Specifications
Model Name	F170PET-T32
Version	1

Customer	
Approved by	Date
Notice: This Specification is subject to change without notice.	

Approved By	Prepared By
ZOE NIEN	ALLEN FANG
2025-12-30	2025-12-30



REVISION HISTORY

Version	ECN No.	Description of Changes	Date	Prepared
0		Draft specification first edition	2023-06-14	Allen Fang
1		Preliminary specification	2025-12-30	Allen Fang



CONTENTS

1. GENERAL DESCRIPTION	4
1.1. INTRODUCTION	4
1.2. FEATURES	4
1.3. APPLICATION	4
2. GENERAL SPECIFICATIONS	5
3. ABSOLUTE MAXIMUM RATINGS	6
4. ELECTRICAL CHARACTERISTICS	7
4.1. LCD MODULE	7
4.1.1. LCD BLOCK DIAGRAM	7
4.1.2. POWER SPECIFICATION	8
4.1.3. LVDS DC ELECTRICAL CHARACTERISTICS	8
4.1.4. LED BACKLIGHT UNIT	9
4.1.5. LCD INPUT TERMINAL PIN ASSIGNMENT	9
4.1.6. LCD BACKLIGHT UNIT	12
4.1.7. PIXEL FORMAT IMAGE	13
4.1.8. THE LCD INPUT DATA FORMAT	13
4.1.9. LCD TIMING CHARACTERISTICS	14
4.1.10. LCD INPUT TIMING DIAGRAM	15
4.1.11. POWER SEQUENCE FOR LCD	16
4.2. TOUCH PANEL	17
4.2.1. TOUCH PIN ASSIGNMENT	17
4.2.2. TOUCH DRIVER	17
5. OPTICAL CHARACTERISTICS	19
6. RELIABILITY TEST ITEMS	23
7. LABEL	23
8. MECHANICAL CHARACTERISTICS	24
9. ENGINEERING DRAWING	26



1. GENERAL DESCRIPTION

1.1.INTRODUCTION

F170PET-T32 is a 17.0" color active matrix TFT LCD module G170ETN01.0 with projected capacitive multi-touch B170PBU-E06 air bonding, with touch driving board ETP-MB-EXC84H4254STAG.

The display format is intended to support the SXGA mode (1280(H) x 1024(V)) screen and 16.2M colors (2 channel LVDS RGB 6-bits+Hi-FRC data) with LED backlight driving circuit.

1.2.FEATURES

- SXGA (1280x1024) resolution
- LVDS Interface with 2pixel/clock
- High-speed response
- 8-bit color depth, display 16.2M colors
- DE (Data Enable) only
- Long life LED backlight (50k hrs)
- RoHS / Halogen Free

1.3.APPLICATION

- TFT LCD monitor

2. GENERAL SPECIFICATIONS

Parameter	Specification	Unit	Remarks
Active Area Size	17.0	inch	
Display Area	337.920(H) x 270.336 (V)	mm	
Outline Dimension	358.50 (H) x 296.50 (V) x 20.56 (D)	mm	D:PCAP+LCM
Weight	1900	g	Typ.
Driver Element	a-Si TFT active matrix	-	
Display Colors	16.2M (RGB 6-bits+Hi-HRC)	Colors	
Electrical Interface	2-ch LVDS	-	
Number of Pixels	1280 (H) x 1024 (V)	pixels	
Pixel Pitch	0.264 (H) x 0.264(W)	mm	
Pixel Arrangement	RGB vertical stripe	-	
Display Mode	Normal White	-	
Color Gamut	72	%	
Touch Technology	Projected Capacitive Multi-Touch Panel	-	
Touch Method	Finger or exclusive pen	-	
Numbers of Touch	10	Points	
Touch Driver	ETP-MB-EXC84H4254STAG	-	
Touch Sensor Glass Type	Strengthening Glass	-	
Touch Controller IC	EETI, EXC80H84	-	
Touch Driver Interface	USB 2.0	-	
Support OS	Windows (Embedded/CE/XP/2000/Vista/7/8/10) / Linux / Android / MAC	-	

3. ABSOLUTE MAXIMUM RATINGS

The followings are maximum values which, if exceed, may cause faulty operation or damage to the unit.

Parameter	Symbol	Min.	Max.	Unit	Remarks
Logic/LCD Drive Voltage	V_{IN}	-0.3	6.0	V	Note 1
Converter Voltage	V_I	-0.3	13.2	V	
Enable Voltage	EN	-0.3	5.5	V	
Dimming Voltage	PWM	-0.3	5.5	V	
Operating Temperature	T_{op}	0	50	°C	Note 2
Operating Humidity	H_{op}	10	90	%RH	
Storage Temperature	T_{st}	-20	60	°C	
Storage Humidity	H_{st}	10	90	%RH	
Touch DC Supply Voltage	USB	-0.3	6.0	V	

Note:


1. Permanent damage to the device may occur if maximum values are exceeded. Function operation should be restricted to the conditions described under Normal Operating Conditions.
2. Maximum Wet-Bulb temperature should be 39°C and no condensation. The relative humidity must not exceed 90% non-condensing at temperatures of 40°C or less. At temperatures greater than 40°C, the wet bulb temperature must not exceed 39°C.

4. ELECTRICAL CHARACTERISTICS

4.1.LCD MODULE

4.1.1. LCD BLOCK DIAGRAM

The following diagram shows the function block of the 17.0 inches wide Color TFT/LCD module.



PCBA Connector:
JAE FI-XB30SSL-HF15
Or Compatible

LED Driver Connector:
Entry 3806K-F06Y-03R
Or Compatible

4.1.2. POWER SPECIFICATION

LCD Input power specifications are as below;

The power specifications are measured under 25°C and frame frequency under 60Hz.

Symbol	Parameter	Min.	Typ.	Max.	Units	Remark
VCC	Logic/LCD Drive Voltage	4.5	5.0	5.5	V	±10%
ICC	Input Current	-	0.59	0.71	A	All Black pattern (VDD=5V, at 75Hz)
PCC	VCC Power	-	2.95	3.54	W	All Black pattern (VDD=5V, at 75Hz)
VCCrp	Allowable Logic/LCD Drive Ripple Voltage	-	-	500	mV p-p	With Panel Loading


4.1.3. LVDS DC ELECTRICAL CHARACTERISTICS

Input signals shall be low or High-impedance state when VDD is off.

It is recommended to refer the specification of SN75LVDS82DGG (Texas Instruments) in detail.

Symbol	Item	Min.	Typ.	Max.	Unit	Remark
VTH	Differential Input High Threshold	-	-	+100	mV	VCM=1.2V
VTL	Differential Input Low Threshold	-100	-	-	mV	VCM=1.2V
VID	Input Differential Voltage	100	400	600	mV	
VICM	Differential Input Common Mode Voltage	1.0	1.2	1.5	V	VTH/VTL=+-100mV

Note: LVDS Signal Waveform



4.1.4. LED BACKLIGHT UNIT

Following characteristics are measured under stable condition at 25°C (Room Temperature)

Symbol	Parameter	Min.	Typ.	Max.	Units	Remark
V_{LED}	Input Voltage	10.8	12	12.6	V	
I_{LED}	Input Current	-	0.8	-	A	100% Dimming
P_{LED}	Power Consumption	-	9.6	-	W	100% Dimming
$I_{INRUSH LED}$	Inrush Current	-	-	5.1	A	V_{LED} rising time ~470us
F_{PWM}	PWM Dimming Frequency	200	-	20K	Hz	Note 1, 2
$V_{PWM DIM}$	Swing Voltage High	3.0	3.3	5.5	V	
	Swing Voltage Low	-	-	0.8	V	
D_{PWM}	Dimming Duty Cycle	10	-	100	%	
I_F	LED Forward Current	-	60	-	mA	Ta=25°C
$V_{LED ON/OFF}$	On Control Voltage	3.0	3.3	5.5	V	Note 3, 4
	Off Control Voltage	-	-	0.8	V	
Operating Life		50,000	-	-	Hrs	Note 5,6

Note :

1. PWM dimming function can be operated by PWM signal. PWM duty cycle can adjust white Luminance. (PWM High: ON and PWM Low: OFF)
2. PWM signal cannot be floating and pull-down to ground when waiting.
3. Enable ($V_{LED On/Off}$) must be turned on late than V_{LED} and PWM Signal.
4. Enable ($V_{LED On/Off}$) must be turned off early than V_{LED} and PWM Signal.
5. If E170ETN01.0 module is driven by high current or high ambient temperature & Humidity condition. The operating life will be reduced.
6. Operating life means brightness goes down to 50% initial brightness. Minimum operation life time is estimated data.


4.1.5. LCD INPUT TERMINAL PIN ASSIGNMENT

The module using a pair of LVDS receiver: SN75LVDS82 (Texas Instruments) or compatible. LVDS is a differential signal technology for LCD interface and high speed data transfer device. Transmitter shall be SN75LVDS83 (negative edge sampling) or compatible. The first LVDS port (RxOxxx) transmits odd pixels while the second LVDS port (RxExxx) transmits even pixels.



Pin	Symbol	Description	Note
1	RXO0-	Negative LVDS differential data input (Odd data)	
2	RXO0+	Positive LVDS differential data input (Odd data)	
3	RXO1-	Negative LVDS differential data input (Odd data)	
4	RXO1+	Positive LVDS differential data input (Odd data)	
5	RXO2-	Negative LVDS differential data input (Odd data)	
6	RXO2+	Positive LVDS differential data input (Odd data)	
7	GND	Ground	
8	RXOCLK-	Negative LVDS differential clock input (Odd data)	
9	RXOCLK+	Positive LVDS differential clock input (Odd data)	
10	RXO3-	Negative LVDS differential data input (Odd data)	
11	RXO3+	Positive LVDS differential data input (Odd data)	
12	RXE0-	Negative LVDS differential data input (Even data)	
13	RXE0+	Positive LVDS differential data input (Even data)	
14	GND	Ground	
15	RXE1-	Negative LVDS differential data input (Even data)	
16	RXE1+	Positive LVDS differential data input (Even data)	
17	GND	Ground	
18	RXE2-	Negative LVDS differential data input (Even data)	
19	RXE2+	Positive LVDS differential data input (Even data)	
20	RXECLK-	Negative LVDS differential clock input (Even data)	
21	RXECLK+	Positive LVDS differential clock input (Even data)	
22	RXE3-	Negative LVDS differential data input (Even data)	
23	RXE3+	Positive LVDS differential data input (Even data)	
24	GND	Power Ground	
25	GND	Power Ground (For AUO test Aging + HVS mode)	
26	NC	No connection	
27	GND	Power Ground	
28	VCC	+5.0V Power Supply	
29	VCC	+5.0V Power Supply	
30	VCC	+5.0V Power Supply	

Note 1: Start from left side



Note 2: Input signals of odd and even clock shall be the same timing.

Note 3: Please follow PSWG.



4.1.6. LCD BACKLIGHT UNIT

Physical interface is described as for the connector on module. These connectors are capable of accommodating the following signals and will be following components.

Connector Name / Description	Lamp Connector
Manufacturer	E&T or Compatible
Connector Model Number	3808K-F06Y-03R or compatible
Mating Model Number	H208K-P06N-02B or compatible


Pin Assignment of LED driver connector

Pin No.	Symbol	Description
1	VCC	12V Input
2	VCC	12V Input
3	GND	GND
4	GND	GND
5	VLED_EN	5V-ON, 0V-OFF
6	VPWM_EN	PWM Dimming




4.1.7. PIXEL FORMAT IMAGE

Following figure shows the relationship of the input signals and LCD pixel format.



4.1.8. THE LCD INPUT DATA FORMAT



Note 1: Normally, DE, VS, HS on EVEN channel are not used.

Note 2: Please follow PSWG

Note 3: 8-bit in


4.1.9. LCD TIMING CHARACTERISTICS

Basically, interface timing described here is not actual input timing of LCD module but output timing of SN75LVDS82DGG (Texas Instruments) or equivalent.

Parameter		Symbol	Min.	Typ.	Max.	Unit
Vertical Section	Period	T _V	1032	1066	1150	T _H
	Active	T _{VD}	1024			
	Blanking	T _{VB}	8	42	126	
Horizontal Section	Period	T _H	780	844	2048	T _{CLOCK}
	Active	T _{HD}	640			
	Blanking	T _{HB}	140	204	1408	
Clock frequency	Period	T _{CLOCK}	14.81	18.52	25	ns
	Frequency	Freq	40	54	67.5	MHz
Frame Rate		F	50	60	75	Hz


Note 1: DE mode only

4.1.10. LCD INPUT TIMING DIAGRAM



4.1.11. POWER SEQUENCE FOR LCD

VDD power and lamp on/off sequence is as below. Interface signals are also shown in the chart. Signals from any system shall be High-impedance state or low level when VDD is off.



Power ON/OFF sequence timing

Parameter	Value			Unit
	Min.	Typ.	Max.	
T1	0.5	-	10	ms
T2	30	40	50	ms
T3	200	-	-	ms
T4	0.5	-	10	ms
T5	10	-	-	ms
T6	10	-	-	ms
T7	0	-	-	ms
T8	10	-	-	ms
T9	-	-	10	ms
T10	110	-	-	ms
T11	0	16	50	ms
T12	-	-	10	ms
T13	1000	-	-	ms



4.2. TOUCH PANEL

4.2.1. TOUCH PIN ASSIGNMENT


CN1						CN2					
PIN	SYMBOLS	PIN	SYMBOLS	PIN	SYMBOLS	PIN	SYMBOLS	PIN	SYMBOLS	PIN	SYMBOLS
1	TX_S2	21	TX20	41	TX0	1	RX_S1	21	RX32	41	RX12
2	TX39	22	TX19	42	TX_S0	2	RX51	22	RX31	42	RX11
3	TX38	23	TX18			3	RX50	23	RX30	43	RX10
4	TX37	24	TX17			4	RX49	24	RX29	44	RX9
5	TX36	25	TX16			5	RX48	25	RX28	45	RX8
6	TX35	26	TX15			6	RX47	26	RX27	46	RX7
7	TX34	27	TX14			7	RX46	27	RX26	47	RX6
8	TX33	28	TX13			8	RX45	28	RX25	48	RX5
9	TX32	29	TX12			9	RX44	29	RX24	49	RX4
10	TX31	30	TX11			10	RX43	30	RX23	50	RX3
11	TX30	31	TX10			11	RX42	31	RX22	51	RX2
12	TX29	32	TX9			12	RX41	32	RX21	52	RX1
13	TX28	33	TX8			13	RX40	33	RX20	53	RX0
14	TX27	34	TX7			14	RX39	34	RX19	54	RX_50
15	TX26	35	TX6			15	RX38	35	RX18		
16	TX25	36	TX5			16	RX37	36	RX17		
17	TX24	37	TX4			17	RX36	37	RX16		
18	TX23	38	TX3			18	RX35	38	RX15		
19	TX22	39	TX2			19	RX34	39	RX14		
20	TX21	40	TX1			20	RX33	40	RX13		

4.2.2. TOUCH DRIVER

Control Board : ETP-MB-EXC84H4254STAG

No.	Item	Specification
1	Touch Controller IC	EXC80H84
2	Number Of Support	10 Fingers Touch
3	FPC Type / Interface	USB / RS232

Interface	Symbol	Condition	Min.	Typ.	Max.	Unit
JP1/JP7	VDD	DC	3.5	5	5.5	V



Connector Pin Configuration

JP1 USB connector

JP1	
1	GND_E
2	VDD
3	GND
4	D+
5	D-

JP5 I2C connector


JP5	
1	GND
2	I2C_SDA
3	I2C_SCL
4	VDD
5	I2C_INT

JP7 RS232 connector

JP7	
1	UR_CTS
2	UR_TX
3	UR_RX
4	UR_RTS
5	GND_E
6	VDD
7	GND

JP3 Tethered active stylus connector

JP3	
1	GND_D
2	TX_PEN
3	VDD
4	GND_D



*JP3 connector is reserved for EETI tethered active stylus:

Type E: Entry-type active stylus

Type T: Tethered USB active stylus

5. OPTICAL CHARACTERISTICS


The optical characteristics are measured under stable conditions of 25°C (Room Temperature)

Item		Unit	Conditions		Min.	Typ.	Max.	Note
View Angle		degree	Horizontal CR=10	Right	70	85	-	1
				Left	70	85	-	
			Vertical CR=10	Upper	70	80	-	
				Lower	70	80	-	
Luminance Uniformity		%	9 points		75	80	-	2, 3
Response Time		ms	Rising		-	3.5	6	4, 6
		ms	Falling			1.5	3	
		ms	Rising + Falling		-	5	9	
Color / Chromaticity Coordinates (CIE 1931)	Red	Rx			0.609	0.639	0.669	4
		Ry			0.302	0.332	0.362	
	Green	Gx			0.290	0.320	0.350	
		Gy			0.599	0.629	0.659	
	Blue	Bx			0.125	0.155	0.185	
		By			0.026	0.056	0.086	
	White	Wx			0.273	0.313	0.343	
		Wy			0.289	0.329	0.359	
White Luminance		cd/m²	At LED=60mA		280	350	-	
Contrast Ratio		-			600	1000	-	
Cross Talk		%	At 75Hz		-	-	1.5	5
Flicker		dB			-	-	-20	7
Color Gamut		%			-	72	-	


Optical Equipment: BM-5A, BM-7, PR880, or equipment

Note 1: Definition of viewing angle

Viewing angle is the measurement of contrast ratio ≥ 10 , at the screen center, over a 180° horizontal and 180° vertical range (off-normal viewing angles). The 180° viewing angle range is broken down as follows; 90° (θ) horizontal left and right and 90° (Φ) vertical, high (up) and low (down). The measurement direction is typically perpendicular to the display surface with the screen rotated about its center to develop the desired measurement viewing angle.



Note 2: The 9 points position




Note 3: The luminance uniformity of 9 points is defined by dividing the maximum luminance values by the minimum test point luminance.

$$\delta_{w9} = \frac{\text{Minimum Luminance of 9 points}}{\text{Maximum Luminance of 9 points}}$$

Note 4: Measurement method

The LCD module should be stabilized at given temperature for 30 minutes to avoid about temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 30 minutes in a stable, windless and dark room.




Note 5: Definition of Cross Talk (CT)

$$CT = |Y_B - Y_A| / Y_A \times 100 \%$$

Where


Y_A = Luminance of measured location without gray level 0 pattern (cd/m^2)

Y_B = Luminance of measured location with gray level 0 pattern (cd/m^2)




Note 6: Definition of response time:


The output signals of BM-7 or equivalent are measured when the input signals are change from "Black" to "White" (falling time) and from "White" to "Black" (rising time), respectively. The response time interval is between 10% and 90% of amplitudes. Refer to figure as below.



Note 7: Sub checker Pattern



Method: Record dBV & DC value with (WESTAR)TRD-100



$$\text{Flicker (dB)} = 20 \log \frac{\text{AC Level(at 30 Hz)}}{\text{DC Level}}$$

6. RELIABILITY TEST ITEMS

Test Item		Condition
1	High temperature/Humidity Bias	50°C, 80% 240hrs
2	High temperature storage test	60°C, 240hrs
3	Low temperature storage test	-20°C, 240hrs
4	High temperature operation test	50°C, 240hrs
5	Low temperature operation test	0°C, 240hrs
6	Thermal Cycle storage test	-20°C(30min)~60°C(30min), 10cycles


7. LABEL

Model No. **F170PET-T32**

條碼

SN 3A Z 20 2 21 0 XXX1

W=14mm



L=32mm

字型:Arial (6)

Code: 128

字型 : Arial(8)

Code1, 2 Production location

Code 3 Production version

Code 4, 5 Production year

Code 6 Production month

Code 7, 8 Production day

Code 9 Production code

Code 10, 11, 12, 13 Serial number

8. MECHANICAL CHARACTERISTICS

Item		Dimension	Unit	Note
Outline Dimension	Horizontal	357.00	mm	PCAP : B170PBU-E06
	Vertical	287.50	mm	
	Depth	2.70	mm	
	Horizontal	358.50	mm	LCD : G170ETN01.0
	Vertical	296.50	mm	
	Depth	17.22	mm	
	Horizontal	82.50	Mm	Touch Driver : ETP-MB-EXC84H4254STAG
	Vertical	33.00	Mm	
	Depth	7.50	mm	
Weight		1900	g	F170PET-T32
Item		Specification		Remarks
PCAP Viewing Area		341.92 mm x 386.50 mm		
PCAP Sensor Area		356.00 mm x 286.50 mm		
PCAP FPC Length		96.70 mm		
PCAP Input method		Finger or exclusive pen		
PCAP Light Transmission		$\geq 90\% \pm 3\%$		
PCAP Operation force		$\leq 10g$		Finger Input
PCAP Hardness of surface		$\geq 7H$		Pressure 500gf test
PCAP Surface Treatment		Haze <4%		BYK Gardner , ASTM D1003



Product Specification

F170PET-T32

Front View



Back View



9. ENGINEERING DRAWING

