

F185PET-Z04

(10-points)(Air Bonding)



Features

- 18.5" PCAP Multi-Touch Display
- 1920 x 1080, 500 cd/m², LVDS Interface
- Supports 10-points touch
- High transparency and excellent display clarity
- Fast response and high sensitivity




Image above for reference only

MADE IN TAIWAN

Specification

Model	F185PET-Z04	
TFT LCD	Inch	18.5"
	Resolution	1920 x 1080 (FHD)
	Signal Interface	LVDS
	Brightness	500 cd/m ² (Typ.)
	Viewing Angle	89/89/89/89
	Contrast	1000 : 1 (Typ.)
	B/L Life Time (Hr)	50K (Min.)
	Backlight Driver	Built-in
PCAP Touch	Structure (Glass Thickness)	G/G (2.75 mm)
	Touch Control Board	ETP-MB-EXC84H4254STAG
	FPC Type	COB
	Interface	USB
	Surface Treatment	Haze < 4%
	Transparency	90 %
	Surface Hardness	≥7H
	Allow Touch Points	≤10 Points
Touch Display	Input Method	Finger, Gloved, Stylus
	Bonding Type	Air Bonding
	View Area (mm)	410.80 x 231.40
	Outline Dimension (mm)	446.05 x 271.18 x 15.85
	Weight	2.02 Kg (Typ.)
	Operating Temperature	-20 ~ 70 °C
	Storage Temperature	-30 ~ 80 °C
	OS	Android, Linux, MacOS, Windows

Dimension



Packing Volume Reference

Packaging	Sample			Full Box	1 Pallet
QTY	1 pc	2 pcs	3 pcs	10 pcs	-
N.W. (Kg)	2.02	4.04	6.06	20.20	-
G.W. (Kg)	3.45	5.47	7.49	22.05	-
Dimension (mm)	525 x 370 x 215	525 x 370 x 215	525 x 370 x 215	530 x 380 x 365	-