

F215PET-T23

(10-points)(Air Bonding)



Features

- **21.5" PCAP Multi-Touch Display**
- **1920 x 1080, 250 cd/m², LVDS Interface**
- **Supports 10-points touch**
- **High transparency and excellent display clarity**
- **Fast response and high sensitivity**




Image above for reference only

MADE IN TAIWAN

Specification

Model	F215PET-T23	
TFT LCD	Inch	21.5"
	Resolution	1920 x 1080 (FHD)
	Signal Interface	LVDS
	Brightness	250 cd/m ² (Typ.)
	Viewing Angle	89/89/89/89
	Contrast	1000 : 1 (Typ.)
	B/L Life Time (Hr)	50K (Min.)
	Backlight Driver	Built-in
PCAP Touch	Structure (Glass Thickness)	G/G (4.0 mm)
	Touch Control Board	ETP-MB-EXC84H5680STAG
	FPC Type	COB
	Interface	USB
	Surface Treatment	Clear
	Transparency	≥85 %
	Surface Hardness	≥6H
	Allow Touch Points	≤10 Points
Touch Display	Input Method	Finger, Gloved, Stylus
	Bonding Type	Air Bonding
	View Area (mm)	477.70 x 269.40
	Outline Dimension (mm)	517.00 x 315.00 x 15.60
	Weight	3.16 Kg (Typ.)
	Operating Temperature	0~ 60 °C
	Storage Temperature	-20 ~ 60 °C
	OS	Android, Linux, MacOS, Windows

Dimension



Packing Volume Reference

Packaging	Sample			Full Box	1 Pallet
QTY	1 pc	2 pcs	3 pcs	7 pcs	-
N.W. (Kg)	3.16	6.32	9.48	22.12	-
G.W. (Kg)	5.36	8.52	11.68	24.32	-
Dimension (mm)	660 x 480 x 230	660 x 480 x 230	660 x 480 x 230	596 x 370 x 414	-