

F215PET-Z21

(10-points)(Air Bonding)



Features

- **21.5" PCAP Multi-Touch Display**
- **1920 x 1080, 500 cd/m², LVDS Interface**
- **Supports 10-points touch**
- **High transparency and excellent display clarity**
- **Fast response and high sensitivity**




Image above for reference only

MADE IN TAIWAN

Specification

Model	F215PET-Z21	
TFT LCD	Inch	21.5"
	Resolution	1920 x 1080 (FHD)
	Signal Interface	LVDS
	Brightness	500 cd/m ² (Typ.)
	Viewing Angle	89/89/89/89
	Contrast	1000 : 1 (Typ.)
	B/L Life Time (Hr)	50K (Min.)
	Backlight Driver	External
PCAP Touch	Structure (Glass Thickness)	G/G (2.70 mm)
	Touch Control Board	ETP-MB-EXC84H5680STAG
	FPC Type	COB
	Interface	USB
	Surface Treatment	Haze < 4 %
	Transparency	90 ±3 %
	Surface Hardness	≥ 7H
	Allow Touch Points	≤10 Points
Touch Display	Input Method	Finger, Gloved, Stylus
	Bonding Type	Air Bonding
	View Area (mm)	476.64 x 268.11
	Outline Dimension (mm)	497.60 x 292.20 x 14.40
	Weight	2.44 Kg (Typ.)
	Operating Temperature	-10~ 60 °C
	Storage Temperature	-20 ~60 °C
	OS	Android, Linux, MacOS, Windows

Dimension



Packing Volume Reference

Packaging	Sample			Full Box	1 Pallet
QTY	1 pc	2 pcs	3 pcs	7 pcs	-
N.W. (Kg)	2.44	4.88	7.32	17.08	-
G.W. (Kg)	4.64	7.08	9.52	19.28	-
Dimension (mm)	660 x 480 x 230	660 x 480 x 230	660 x 480 x 230	596 x 370 x 414	-