

F238PET-T21

(10-points)(Air Bonding)



Features

- 23.8" PCAP Multi-Touch Display
- 1920 x 1080, 250 cd/m², LVDS Interface
- Supports 10-points touch
- High transparency and excellent display clarity
- Fast response and high sensitivity




Image above for reference only

MADE IN TAIWAN

Specification

Model	F238PET-T21	
TFT LCD	Inch	23.8"
	Resolution	1920 x 1080 (FHD)
	Signal Interface	LVDS
	Brightness	250 cd/m ² (Typ.)
	Viewing Angle	89/89/89/89
	Contrast	3000 : 1 (Typ.)
	B/L Life Time (Hr)	30K (Min.)
	Backlight Driver	External
PCAP Touch	Structure (Glass Thickness)	G/G (4.0 mm)
	Touch Control Board	ETP-MB-EXC84H5680STAG
	FPC Type	COB
	Interface	USB
	Surface Treatment	Clear
	Transparency	≥85 %
	Surface Hardness	≥6H
	Allow Touch Points	≤10 Points
Touch Display	Input Method	Finger, Gloved, Stylus
	Bonding Type	Air Bonding
	View Area (mm)	528.60 x 298.00
	Outline Dimension (mm)	570.00 x 343.00 x 16.30
	Weight	4.05 Kg (Typ.)
	Operating Temperature	0 ~ 50 °C
	Storage Temperature	-20 ~ 60 °C
	OS	Android, Linux, MacOS, Windows

Dimension



Packing Volume Reference

Packaging	Sample			Full Box	1 Pallet
QTY	1 pc	2 pcs	3 pcs	-	-
N.W. (Kg)	4.05	8.10	12.15	-	-
G.W. (Kg)	6.25	10.30	14.35	-	-
Dimension (mm)	660 x 480 x 230	660 x 480 x 230	660 x 480 x 230	-	-