

TITLE : VISUAL INSPECTION CRITERIA FOR ALL CUSTOMER

- 18.5" MODULE A-Grade

DV185FHM-R00

BEIJING BOE DISPLAY THCHNOLOGY

SPEC. NUMBER
S45-8064PRODUCT GROUP
TEST-MODULEREV.
OISSUE DATE
2013.01.09PAGE
1 OF 9

B2010-8002-O(1/3)

A4(210 X 297)

 京东方 BOE		PRODUCT GROUP		REV.	ISSUE DATE
		TEST-MODULE		O	2013.01.09
REVISION HISTORY					
REV	ECN NO.	DISCRIPTION OF CHANGES		DATE	PREPARED
O	-	INITIAL RELEASE		2013/1/9	张志波
SPEC. NUMBER S45-8064		SPEC. TITLE	VISUAL INSPECTION CRITERIA FOR CUSTOMER (18.5" MODULE A-Grade)		PAGE 2 OF 9
B2010-8002-O(2/3)		A4(210 X 297)			

 京东方 BOE	PRODUCT GROUP		REV.	ISSUE DATE
	TEST-MODULE		O	2013.01.09
1.0 Introduction				
1.1 Scope				
This Incoming Inspection Standard shall be applied to TFT-LCD modules(hereafter call the "LCMs") supplied by BOE(hereafter called the "Supplier") to its Customer.				
1.2 Incoming Inspection Right				
The Customer shall have the right to conduct at its own cost and expense,an incoming inspection of the LCMs at the destination specified in the relevant B/L(Bills of Lading) in accordance with the LCM's specifications separately agreed upon and the inspection criteria set forth in this article.				
The customer shall notify the Supplier in writing of the inspection results(acceptance or rejectance) in accordance with the said Incoming Inspection Standard within 40 days from the date of the B/L.				
Should the Customer fail to notify the results to Supplier with 40 days period, the right to reject the LCMs shall then lapse and the said LCMs shall be deemed to have been accepted by the Customer.				
1.3 Handling Precautions				
- LCM Devices are made of fragile material such as Glass and plastic and may be broken or cracked if dropped it. So PLEASE handle them with care. - DO NOT press the area covered with PET or such materials.These are weak point of LCMs since of TCPs(Drive Ics) and PWBs. - PLEASE support the Bezel with your finger when connecting the interface cable. - PLEASE DO NOT touch the surface of the Glass(Polarizer). - PLEASE wear the Wrist Strap when handling. Semiconductive devices are included in the LCMs and they should be handled with care to prevent any electrostatic discharge(ESD).				
- PLEASE keep the LCMs in the specified,original packing boxes when storage. - DO NOT stack the LCMs too high without wrapping material such as AIR CAP. - Before use the LCMs,PLEASE check the Engineering specification. - LCMs contain a small amount of Liquid Crystal and Mercury.PLEASE follow local ordinances or regulations for disposal.				
</				

 京东方 BOE	PRODUCT GROUP		REV.	ISSUE DATE
	TEST-MODULE		O	2013.01.09
2.0 Generals				
2.1 Sampling Method				
Unless otherwise agreed upon in writing the sampling inspection shall be applied to the Customers' incoming inspection				
2.1.1 Acceptable quality level (AQL) : Major defect: AQL=0.65% Minor defect: AQL=1.5%				
Note 1) Major defect The major defect is a defect that is likely to result in product failure, or reduction in the product's intended usage. For example: electrical failure, deformation etc.				
Note 2) Minor defect The minor defect is a defect that has little bearing on the effective use or operation of the product. For example: dot defect, mura etc.				
2.2 Inspection Environment				
2.2.1 Ambient conditions				
a. Ambient Temperature : 25±5℃ b. Relative Humidity : 65±5%RH c. Ambient Illumination : Light on inspection: 150±50 Lux Appearance inspection: 500±200Lux				
2.2.2 Viewing Distance				
The distance between the LCM and the inspector's eyes shall beat least 30cm- 50cm				
2.2.3 Viewing Angle				
performing in front of the panel [Vertical] : ± 25 degree [Horizontal] : ± 40 degree				
2.2.4 Inspection Area				
Display Area (Active Area)				
2.3 Definitions				
2.3.1 Dark / Bright Spots				
Points on display which appear dark/bright and usually result from the contamination. These defects do not vary in size or intensity (contrast) when contrast is varied.				
2.3.2 Dark / Bright Lines				
Lines on display which appear dark/bright and usually result from the contamination.				
2.3.3 Polarizer Scratch				
Lines on display which are seen across a darker background and do not vary in size.				
2.3.4 Polarizer Dent				
White spots on display which appear against a darker background and do not vary in size				
2.3.5 Bright Dot Defects				
Dots(sub-pixels) on display which appear bright in the display area and visible through the 5%ND filter at Black Pattern and L64 gray scale pattern.				
SPEC. NUMBER S45-8064		SPEC. TITLE		VISUAL INSPECTION CRITERIA FOR CUSTOMER (18.5" MODULE A-Grade)
PAGE 4 OF 9		B2010-8002-O(3/3)		


 京东方 BOE	PRODUCT GROUP		REV.	ISSUE DATE
	TEST-MODULE		O	2013.01.09
2.3.6 Dark Dot Defects Dots(sub-pixels) on display which appear dark in the display area at R,G,B Color Pattern. 2.3.7 Line Defects All line defects on display which appear brigh/dark such as vertical, horizontal, or cross lines. 2.3.8 Mura Mura on display which appears darker / brighter against background brightness on parts of display area. 2.3.9 BM Defects Bright(white) Points on display which are off BM(Black Matrix). 2.3.10 Visual Inspection Inspection for LCM when the unit turns on. 2.3.11 Appearance Inspection External inspection for LCM when the unit turns off. 2.3.12 Others Defects which cannot be classified into the above defect definitions.				
SPEC. NUMBER S45-8064	SPEC. TITLE	VISUAL INSPECTION CRITERIA FOR CUSTOMER (18.5" MODULE A-Grade)		PAGE 5 OF 9
B2010-8002-O(3/3)				A4(210 X 297)

3.0 Inspection Criteria

3.1 Visual Inspection Criteria


ITEMS	DETAILS		INSPECTION CRITERIA
Sub Pixel Defects	Bright Sub Pixel Defect		$N \leq 0$
	Dark Sub Pixel Defect		$N \leq 5$
	Bright+Dark Sub Pixel Defect		$N \leq 5$
	Defect Distance	Bright & Bright	-
		Dark & Dark	$L \geq 5\text{mm}$
	2 Adjacent Bright Sub Pixel Defect		$N \leq 0$
	2 Adjacent Dark Sub Pixel Defect		$N \leq 0$
	3 Adjacent Bright Sub Pixel Defect		$N = 0$
	3 Adjacent Dark Sub Pixel Defect		$N = 0$
Line Defects	Bright Line, Dark Line		$N = 0$
Displayed Screen	Black/Bright Spot (Hair, Lint, Etc)	Circular Type	$D \leq 0.2$ Ignore $0.2 < D \leq 0.5, N \leq 4$
		Linear Type	$W \leq 0.03$ Ignore $0.03 < W \leq 0.1, L \leq 2.0, N \leq 3$
	Polarizer Dent/Bubble Scratch	Circular Type	$D \leq 0.2$ Ignore $0.2 < D \leq 0.5, N \leq 3$
		Linear Type	$W \leq 0.03$ Ignore $0.03 < W \leq 0.5, L \leq 2.0, N \leq 3$
	Glass Broken, Stain		Could not be seen by human eyes
	Circular White Mura, Lumination Mura, Black/White Mura, etc.		2% ND Filter in 50% of total gray pattern or refer to Limit Sample
Flicker			Adjust flicker to best at the center of display area
Crosstalk			Should not be perceived

Note 1) D = Diameter, L = Length, W = Width, N = Number



Note 2) Circular Type : long axis/short axis ≤ 2
 Linear Type : long axis/short axis > 2

Note 3) Dot which is invisible through 5% ND filter or smaller than 1/2 of sub-pixel size will not counted as " 1 dot " Defect.



ITEM	DETAILS	INSPECTION CRITERIA
Bezel	Scratch, Contamination	Could not be seen by human eyes
	Assembly	Should be assembled correctly with panel
	Bending Area	Should be in mechanical spec.
	Color Change, Bent	Nothing
Plastic	Break, Modification	Not allowed
	Scratch, Contamination	Could not be seen by human eyes
	Burr	Not allowed
Cable	Scratch	Could not be seen by human eyes
	Cable Position, Connecting Method	should be in correct position
Signal / Power Input Connector	Break	Not allowed
Connector Others	Looseness	Not allowed
Screw	Improperness, Loosenss	Not allowed
Lable	No Lable, Reversed Lable Attach, Long Distance Attach	Not allowed
	Split, Contamination, Vagueness	At least, it should be legible character by character

 京东方 BOE	PRODUCT GROUP		REV.	ISSUE DATE
	TEST-MODULE		O	2013.01.09
4.0 RMAs				
4.1 Verification				
The supplier can verify the defective LCMs to segregate the responsibilities at customer's facility or can request the Customer to ship the defective LCMs to assigned place for verification				
This verification result shall be agreed mutually by the Customer and Supplier.This result can be corrected or changed after detail failure analysis at Supplier's facilities.				
4.2 Supplier Induced Defects				
All of the Supplier induced defective LCMs shall be returned to the Supplier for repair or replacement.				
Before return the defective LCMs, the Customer needs Supplier's confirmation with RMA Number.				
All of the returned LCMs shall be returned to the Customer within agreed time period.				
4.3 Customer Induced Defects				
The Customer can return the customer induced defective LCMs to the Supplier for repair.				
The repair cost for Customer induced defective LCMs shall be agreed with both parties, Customer and Supplier				
4.4 RMA LCMs' shipment				
4.4.1 For the Chinese Customers				
BOE RMA LCMs would be returned to BEIJING				
4.4.2 For the Korea Customers				
BOE RMA LCMs would be returned to Korea.				
4.4.3 For the other countries' Customers				
If there is a repair center in the Customer's country, BOE RMA LCMs shall be returned to the repair center.				
If there is no repair center in the Customer's country, BOE RMA LCMs shall be returned to BEIJING.				

 京东方 BOE	PRODUCT GROUP		REV.	ISSUE DATE
	TEST-MODULE		O	2013.01.09
5.0 Warranty				
5.1 Warranty Period				
In-warranty period is Eighteen(18) Months from manufacturing month of LCM.				
Note)				
a. Eighteen months are composed of twelfth months in-warranty period and sixth months distribution period.				
b. The manufacturing Month is on the LCMs as Supplier's serial No.				
5.2 Repair Warranty				
Repair warranty is Eighteen(12) Months from repaired month for repaired LCMs.				
Note)				
a. The Label for repair will be added after repairing.				
5.3 Warranty avoidance				
The warranty will be avoided in cases of below:				
a. When the warranty period is expired.				
b. The Customer induced defective LCMs.				
c. When the LCMs were repaired by 3rd party without Supplier's approval.				
d. When the LCMs were treated like Disassemble and Rework by the Customer and/or Customer's representatives without Supplier's approval.				
6.0 Others				
If any problems arise with the LCMs supplied by supplier, the customer and supplier will cooperate and make efforts to solve it with mutual confidence and respect.				
SPEC. NUMBER S45-8064	SPEC. TITLE	VISUAL INSPECTION CRITERIA FOR CUSTOMER (18.5" MODULE A-Grade)		PAGE 9 OF 9
B2010-8002-O(3/3)				A4(210 X 297)